



C110

Exceptional video quality for work and beyond.



True Excitement

The new ASK Proxima C110 is the first digital projector in the ASK Proxima line designed to deliver great performance during the workday and shine on into an entertaining evening. The C110 marks the spot where valuable business tools and versatile performance options converge into a projector of exceptional quality. At work, school, or anywhere else you want to share information.

True Digital Video Quality

You get more out of your meeting room projector with the true digital video quality the ASK Proxima C110 offers. With the C110, you can enjoy crisp images and full color, whether you're looking at this year's numbers or the year's best picture. The latest digital processing technology (DLP™) from Texas Instruments® provides a stunning 2000:1 contrast ratio and automatic deinterlacing, for smooth, true-to-life images that jump off the screen and pull your audience in. Impress your audience during the workday, and your friends and family in the evening with 1700 max ANSI lumens of brightness. And with a 4000-hour lamp life, you can count on a viewing experience that will last a lifetime.



Get more out of your meeting with true digital video quality.

True Connectivity

The C110 ensures you can connect and perform no matter where you are. Connect your laptop, PDA, DVD player, cable or satellite TV system, digital camera, or game console for versatile viewing from a variety of sources. And, get ready to take advantage of wireless freedom with the C110.

True Ease of Use

Like all ASK Proxima projectors, the C110 is designed for easy set up and use. Get started right away with intuitive keypads and menus. One simple keypad delivers one-touch operation, so there's no need to refer to the user manual for common tasks; just scroll through the menu and select. Hooking up is simple with color-coded connections. And, at a mere, 6.8 lbs/3.1 kg, the C110 is super-portable, making it easy to carry from work and beyond.



Use the C110 for versatile viewing beyond work.



TECHNICAL SPECIFICATIONS*

Native Resolution	• SVGA 800 x 600
Display Technology	• DLP™ by Texas Instruments®: 0.55" SVGA DDR DMD
Input Sources	• Computer (M1-DA); Video (S-Video 4-pin mini DIN and Composite RCA); Audio (Stereo RCA)
Output Sources	• Monitor Out (VESA); Audio (3.5mm)
Computer Compatibility	• SVGA, VGA, XGA, Macintosh®
Video Compatibility	• NTSC, PAL, SECAM, DVI, HDTV (1080i, 720p, and 480p)
Brightness	• 1700 max ANSI lumens
Contrast Ratio	• 2000:1 full on/full off
Number of Colors	• 16.7 million
H-Synch Range	• 31.5 – 80 kHz
V-Synch Range	• 50 – 85 Hz
Dot Clock	• 20 to 95 MHz
Digital Keystone Correction	• +/- 20° vertical correction; data/video
Projection Lens	• Zoom lens with manual focus and manual zoom adjust
Zoom Ratio	• 1.2:1
Throw Ratio	• 1.89 to 2.27:1 (D/W), 1.51 to 1.82:1 (D/D)
Minimum Projection Distance	• 1.5 m (maximum distance 9.8 m)
Aspect Ratio	• 4:3 and 16:9
Image size (diagonal)	• 2.7' to greater than 21.6' (0.8 m to greater than 6.5 m)
Projection Methods	• Front, ceiling, rear
Audio	• 2.5-Watt mono
Control	• Projector keypad; IR remote control
Lamp*	• 200W SHP/4000 hours
Dimensions	• 9.8" (W) x 12.9" (L) x 4.2"(H) / 24.9cm x 32.7cm x 10.6cm
Weight	• 6.8 lbs/3.1 kg
Power Consumption	• 200 watt typical/250 watt maximum
Power Supply	• 100V – 240V at 50 – 60 Hz
Operating Temperature	• 5° to 40° C at sea level (0 to 10,000'); 41° – 104° F
Menu Languages	• English, Norwegian, Spanish, Italian, Portuguese, German, French, Chinese (simple), Chinese (traditional), Japanese, Korean, Russian
Audible Noise	• 39 dB (standard mode) • 37 dB (whisper mode)
Approvals	• UL, c-UL, TUV GS, CE, GOST, C-Tick, NOM, IRAM, FCC B, CISPR22 /EN55022, EN 55024 / CISPR 24, CB certified according to IEC60950 / EN60950: 1997, P(SE), MIC
Lamp Warranty	• 90 days
Product Warranty	• 1 year parts and labor
Accessory Warranty	• 1 year

*Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude or rapidly switching the projector on and off.

+ASK Proxima reserves the right to alter product offerings and specifications at any time without notice.

++Product warranty may vary per region.

SHIPS STANDARD WITH:

- Lens cap
- Wireless Navigator Remote Control (including batteries)
- Computer cable
- RCA Video and Audio cable
- Power cord
- SCART adapter (EMEA Only)
- Projector System CD includes: multi-language User Guide, Quick Start Card, URL/service information/accessories after market
- User Guide (printed version)
- Quick Start Card (printed version)

ORDERING INFORMATION

Optional Accessories

HW-PRESENTER	Presenter Remote
HW-PRESENTER-RF	Presenter RF Remote
HW-CONDUCTOR+	Conductor Plus Remote
LP-LITESHOW	LiteShow Wireless Connection
SP-DVI-D	Digital Computer Cable
SP-M1-ADPT	M1 to Component Adaptor
CA-ATA-019	ATA Roller Case
CA-C230	Organizer Soft Case
SP-CEIL-UNIV	Ceiling Mount Kit
SP-LOCK-B	PC Guardian Projector Cable Lock
A650	50" Portable Projection Screen
HW-DLXSCRN	60" Deluxe Insta-Theatre Screen
HW-WALLSCR84	84" Pull-Down Screen
SP-LAMP-018	Replacement Lamp

SERIOUS COMMITMENT

ASK Proxima's dedication to quality and customer satisfaction is reflected in service options that will bring you a greater return on your investment. ASK Proxima projectors come with a standard limited factory warranty, including parts and labor and a 90-day lamp replacement. Our customer support offers you premium service and convenience, whatever your needs.

For service program details in your region, please visit:
www.infocus.com/service/service_offerings

ASK Proxima

www.askproxima.com

InFocus Corporate Headquarters: 27700B SW Parkway Avenue
Wilsonville, Oregon 97070-9215, USA • Phone: (1) 503-685-8888
(1) 800-294-6400 • Fax: (1) 503-685-8887

In Europe: InFocus International BV • Strawinskylaan 585 • 1077 XX Amsterdam
The Netherlands • Phone: (31) 20 5792000 • Fax: (31) 20 5792999
Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: 238A Thomson Road • #18-01/04 Novena Square
Singapore 307684 • Telephone: (65) 6334-9005 • Fax: (65) 6333-4525